FOREST BRIGHT
ARCHITECTURAL WOOD DOOR

HPDL COMPOSITE PARTICLEBOARD CORE FLUSH WOOD DOOR | 45-MIN POSITIVE PRESSURE

Models	CPB-H-45		
Maximum Size	ITS-WH MAX 45min, 1-3/4" or 2" thick		
		CAT A Positive Pressure	CAT B Positive Pressure
	Single	4'0"x8'0"	4'0"x8'0"
	Pairs	N/A	N/A
Faces	High pressure decorative laminate (HPDL) or Thermal Fused Laminate (TFL).		
Crossbands	High Density Fiberboard (HDF).		
Core	Composite Particleboard core with mineral board layer.		
Weight	Approx. 6.1 lbs. per square foot (1-3/4").		
Vertical Stiles	1-3/8" SCL stiles with customized matching color PVC edgebanding. Intumescent strip concealed in door edge (CAT A).		
Top Rail	1-3/8" SCL top rail with customized matching color PVC edgebanding. Intumescent strip concealed in door edge (CAT A).		
Bottom Rail	1-3/8" SCL bottom rail with customized matching color PVC edgebanding.		
Factory Finish	N/R		
Acoustical Rating	STC 31 (operable, tested with seals & gaskets).		
Machining	All hardware preparations, including pre-drilled hinge pilot holes and mortise cutouts, are factory-machined strictly per approved shop drawings and manufacturer templates.		
Cutouts	5-1/2" minimum distance from door edge and the minimum distance between lite and lock cut out is 3-1/4".		
Bevel Option	Non-bevel, 1 side bevel or 2 side bevels, 1/8" at 2" as standard.		
Quality Standard	ANSI/WDMA I.S.1-A standard; AWS Section 9 available on request; bonded core construction standard.		
WDMA Performance Level	Heavy Duty. Blocking required for face-applied hardware at extra heavy duty.		
Warranty	Limited Lifetime, Interior use only.		
Cross Section			



C US
Intertek

Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.
** Fire-Rated doors will be constructed per label service listing and may deviate from above.*

info@forestbright.com
www.forestbright.com