FOREST BRIGHT
ARCHITECTURAL WOOD DOOR

HPDL HOLLOW CORE FLUSH WOOD DOOR | NON-RATED

Models	HC-H-00	
Maximum Size	Non-rated, 1-3/8", 1-3/4" or 2" thick	
		Non-Rated
	Single	4'0"x10'0"
	Pairs	8'0"x10'0"
Faces	High pressure decorative laminate (HPDL) or Thermal Fused Laminate (TFL).	
Crossbands	High Density Fiberboard (HDF).	
Core	Expanded honeycomb paper core.	
Weight	Approx. 2.2 lbs. per square foot (1-3/4").	
Vertical Stiles	1-3/8" SCL stiles with customized matching color PVC edgebanding.	
Top Rail	1-3/8" SCL top rail with customized matching color PVC edgebanding.	
Bottom Rail	1-3/8" SCL bottom rail with customized matching color PVC edgebanding.	
Factory Finish	N/R	
Machining	Machining preparation per hardware manufacturer's templates.	
Lite	Vision lites max. height 36", one cutout per door, with special liner built into core; 6" minimum lite-lock margins.	
Bevel Option	Non-bevel, 1 side bevel or 2 side bevels, 1/8" at 2" as standard.	
Quality Standard	ANSI/WDMA I.S.1-A standard.	
WDMA Performance Level	Standard Duty. Blocking / lock block required at all hardware locations.	
Warranty	1 year. Interior use only.	
Cross Section		



Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.
** Fire-Rated doors will be constructed per label service listing and may deviate from above.*

info@forestbright.com
www.forestbright.com