FOREST BRIGHT
ARCHITECTURAL WOOD DOOR

HPDL TUBULAR PB CORE FLUSH WOOD DOOR

NON-RATED

Models	TPB-H-00	
Maximum Size	Non-rated, 1-3/8", 1-3/4" or 2" thick	
		Non-Rated
	Single	4'0"x10'0"
	Pairs	8'0"x10'0"
Faces	High pressure decorative laminate (HPDL) or Thermal Fused Laminate (TFL).	
Crossbands	High Density Fiberboard (HDF).	
Core	Tubular Particleboard core.	
Weight	Approx. 3.9 lbs. per square foot (1-3/4").	
Vertical Stiles	1-3/8" SCL stiles with customized matching color PVC edgebanding.	
Top Rail	1-3/8" SCL top rail with customized matching color PVC edgebanding.	
Bottom Rail	1-3/8" SCL bottom rail with customized matching color PVC edgebanding.	
Factory Finish	N/R	
Machining	Machining preparation per hardware manufacturer's templates.	
Cutouts	5" minimum distance from door edge and the minimum distance between lite and lock cut out is 3-1/4".	
Bevel Option	Non-bevel, 1 side bevel or 2 side bevels, 1/8" at 2" as standard.	
Quality Standard	ANSI/WDMA I.S.1-A standard.	
WDMA Performance Level	Heavy Duty; Extra Heavy Duty available with additional blocking. Blocking / lock block required at all hardware locations.	
Warranty	1 year. Interior use only.	
Cross Section		



Note: Doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.
** Fire-Rated doors will be constructed per label service listing and may deviate from above.*

info@forestbright.com
www.forestbright.com